

FUJI HEAVY INDUSTRIES, LTD.

EXECUTIVE ORDER A-002-0161 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			STANDA (LEV≖lov ULI	JST EMISSION ARD CATEGORY V emission vehicle; EV=ultra LEV; V=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	19	9FJXJ02.5NVD			PC and LDT ≤ 6,000 pounds GVW (PC; LDT 3,751 – 5,750 pounds LVW)					150K / 150K	Gasoline				
No.		EVAPORATIVE N			io.		PECIAL FEATURES & "= not applicable on CONTROL SYSTEMS (ECS)				OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S				
1	9FJ	9FJXR01254CK			1	TWC(2), HAFS,	HO2S,	SFI, EGR, OI	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed						
2	9FJ	9FJXR01254CP			2		•		ÄIR MFI/SFI= multiport						
3		•			3		*								
4		*			4		*		diagnostic prefix 2=parallel (2) suffix=series						
EVA		ECS				VEHICLE			CT TO SFTP		···				
No.	<u> l .</u>	No. SIZE (L)				MAKES & MODELS	ES & MODELS STANDARDS ARE <u>UNDERLINED</u>								
1		1 2.5				SUBARU: (PC) LEGACY AWD (2.5I, 2.5I-Ltd.), LEGACY WAGON AWD 2.5I									
1		1 2.5			SUBARU: (LDT 3,751-5,750 pounds LVW) OUTBACK WAGON AWD (BASE, Ltd.)										
2		1 2.5				SUBARU: (LDT 3,751-5,750 pounds LVW) FORESTER 2.5X, FORESTER 2.5XS									
*		* *				•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/ml]) RAF = * RAF ≃ *	NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides r of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]≠2/5 day diurnat+hot-soak R. [g/mi]=running loss ORVR [g/gallon dispensed]≠on-board refueling vapor recovery g=ram											
	STD STD PC/LDT1 LDT2		NMOG	NMHC CERT	NMHC STD [g/mi]	mg=millig	ram mi:	=mile K=	1000 miles	F=de	egrees F	ahrenheit	SFTP=sup	plemental fe	deral test pr	ocedure	
PC/LD			CERT			CO	[g/mi]	NO	Ox [g/mi]		HCHO	[mg/mi]	PM [g/mi]	Hwy NO	x [g/mi]	
0.038	3 0.	.047	[g/mi]	[g/mi]	[9]	CERT	STD	CER	r ST	D C	CERT	STD	CERT	STD	CERT	\$TD	
	@ 50K		•	•	*		*	*			*	*	*	•	•	•	
	@ UL		0.007	*	* 0.010		1.0	0.01	0.0	2	0.5	4	*	0.01	0.01	0.03	
	@ 50°F & 4K		0.015	•	0.020	0.3	1.0	0.01	0.0	2	1	8	*	•	•	•	
CO [LE LE		ier 1, TLEV)				CO [g/mi] (composite)		NMHC+NOx [g/ml] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	K	SFTP 2	= @ UL (Tie	r 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD	
CERT	2.1			SFTP 1	*	•	*	•	0.02	0,14	2	.6 8.0	0.02	2 0.20	0.01	2.7	
STD	10.0			SFTP 2	*	*	•	•	*	*	,	•	•	•	*	*	
@ UL	E/	VAPOR/	ATIVE FAI	VILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
W OL	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	. ORV	R 3-D	2-D	RL	ORVR	
CERT	0.22	0.2	4 0.00	0.02	0.25	0.19	0.00	0.01	*	*	*	*		•	•		
STD	0.35	0.3	5 0.05	0.20	0.50	0.50	0.05	0.20	• [*	1		*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are granted a partial zero-emission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962 (c)(2).

BE IT FURTHER RESOLVED: That the listed vehicle models have been certified on the condition that the manufacturer provide all the on-board diagnostic data required by 13 CCR Section 1968.2 (i)(2.5.2) by March 7, 2008. Failure to submit the required misfire probability of detection charts by the specified date, or failure of the submitted data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

FUJI HEAVY INDUSTRIES, LTD.

EXECUTIVE ORDER A-002-0161 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 22 day of January 2008.

Annette Hebert, Chief

Mobile Source Operations Division